

Canadian Council of Independent Laboratories

Determining the Percentages of Fractured Particles in Coarse Aggregate ASTM D5821 - 13

APPARATUS / SECTION 5

| 1. Balance / Clause 5.1 – Accurate and readable to within 0.1% of the test sample mass At any point within the range of use | |
|--|--|
| 2. Sieves / Clause 5.2 - Conforming to ASTME11 | |
| 3. Splitter / Clause 5.3 | |
| 4. Spatula / Clause 5.4 | |
| SAMPLE PREPARATION / CLAUSE 6.1 & SECTION 7 | |

- a. Field Sample / Clause 6.1
 - Sampled in accordance with ASTM D75
- b. Sample Preparation / Section 7
 - Sample sufficiently dried to separate CA and FA material on 4.75mm (No. 4) sieve?
 - R/4.75mm material reduced in accordance with ASTM C702 to appropriate test size?
 - Mass of sample shall be at least large enough so that the largest particle Is not more than 1% of the sample mass?

Or

The test sample shall be a least as large as indicated in chart below, whichever is smaller?

| Nominal Maximum Size | Minimum Test Sample Mass, |
|--------------------------|---------------------------|
| Square Opening, mm (in.) | gms (Approx. lb) |
| 9.5 (3/8) | 200 (0.5) |
| 12.5 (½) | 500 (1.0) |
| 19.0 (¾) | 1,500 (3.0) |
| 25.0 (1.0) | 3,000 (6.5) |
| 37.5 (1 ½) | 7,500 (16.5) |
| 50 (2.0) | 15,000 (33.0) |
| 63 (2 1/2) | 30,000 (66.0) |
| 75 (3) | 60,000 (132) |
| 90 (3 ½) | 90,000 (198) |

Note 1: Samples of nominal maximum size 19.0 mm or larger, the portion passing 9.5 mm sieve may be further reduced in accordance with the ASTM C702 to a minimum of 200 g. Determine fracture count on both portions and determine weighted average percentage of fractured particles (Refer to clause 7.3).



Canadian Council of Independent Laboratories

Determining the Percentages of Fractured Particles in Coarse Aggregate ASTM D5821 - 13

PROCEDURE / SECTION 8

| a. b. c. | Washed sample over 4.75 mm or smaller designated sieve and oven dried? Determined mass to the nearest 0.1% of the original dry sample mass? Spread sample on a suitably large clean flat surface area and separate into two categories? Fractured particles having the required number of fractured faces according to specifications? | |
|----------------|--|--|
| | Definitions: | |
| | Fractured Face: Fractured face representing at least ¼ of the <u>maximum</u> cross- sectional area of the particle. Face has a sharp or slightly blunt edge. | |
| | Fractured Particle: Particle having at least the minimum number of fractured faces specified. | |
| | Determine the mass or count of particles in the fractured particle category and the mass or count of the non fractured category? | |
| REPORT / | SECTION 9 | |
| a. | Mass or count percentage reported to the nearest 1%? | |
| | Note 2: Refer to clause 9.1 for further details in reporting. | |
| COMMENTS: | | |